

Service:	File(s) to change:	What it was	Replace with:	Source of the info:	Notes:
Sendmail	/etc/rc.conf	(blank)	sendmail_enable="NO"	Jail manpage, Setting up the host environment	Keeps sendmail from listening externally, but keeps the internal emails coming.
Syslogd	/etc/rc.conf	(blank)	syslogd_flags="-ss"	Jail manpage, Setting up the host environment	There's a nice section in the jail manpage on centralized logging...
Rpcbind	/etc/rc.conf	(blank)	rpcbind_enable="NO"	Jail manpage, Setting up the host environment	Rpcbind may be required for NFS.
Samba	/usr/local/etc /smb.conf	(blank)	interfaces = 192.168.1.100/24 127.0.0.1 socket address = 192.168.1.100 bind interfaces only = yes	Section 6 wiki	You can also disable if you're not using WINS, but I had bad luck with that.
Samba (alternate option)	/etc/rc.conf	samba_enable="YES"	smbd_enable="YES"	Section 6 wiki	After I did this, I had to add the FreeBSD samba host to the lmhosts file in windows to allow hostname resolution to work.
Bacula-dir	/usr/local/etc /bacula-dir.conf, {Director} section	(blank)	DirAddress=192.168.1.100	<a href="http://www.bacula.org/en/rel-manual/Bacula_Security_Issues.html">http://www.bacula.org/en/rel-manual/Bacula_Security_Issues.html</a>	
Bacula-fd	/usr/local/etc /bacula-fd.conf {FileDaemon} section	(blank)	FDAddress=192.168.1.100	""	
Bacula-sd	/usr/local/etc /bacula-sd.conf {Storage} section	(blank)	SDAddress=192.168.1.100	""	
Sshd		(blank)	ListenAddress 192.168.1.100	Section 6 wiki	

\*I had to replace NTPd with OpenNTP because NTPd doesn't seem to have a way to change the listen address without source code modification.